



29	Power cord	H05RN-F 3G1.0mm <sup>2</sup> *1.6m	1
28	Pinching screw	φ8*35mm/PA	2
27	Plastic gasket	φ8mm Rubber	2
26	Protecting bush	PVC black	2
25	Rubber feet	PP	4
24	Steel pipe	∅16*1.0mm	1
23	Temperature controller	250V AC 16A 85° C	1
22	Rotary switch	250V/15A/VDE	1
21	Internal stent	SECC	3
20	Inner casing	SECC	1
19	Plug	PVC	6
18	Air inlet grill	PA black	1
17	Motor	YJF61-20 220-240V/50Hz/40W	1
16	Fan	∅160mm	1
15	Fan fixing plate	φ4*28*1.0mm/SECC	1
14	Outer casing	SPPC	1
13	Power cord fastener	P69	1
12	Handle	ABS black	1
11	Handle cover	ABS black	1
10	Thermostat knob	PA66 black	1
9	Switch knob	PA66 black	1
8	Indicator-lamp cover	PC	1
7	Control box	ABS Black	1
6	Re-set thermostat	250V 16A 45° C	1
5	Thermal link plate	SECC	1
4	Thermal link	250V/10A/TP121°C	1
3	Fixed bin box	SECC	1
2	Tubular electric heating element	220V-240V 50HZ 2000W	1
1	Front grill	SPPC	1
Key No.	Description	Material / Specifications	QTY

Project	Part No.	Parameter
BGP1505-02-17		

Designer	Standard	Units	m m
Check	Approval	Scale	Parameter

Ningbo Baogong Electrical Appliance Co., Ltd.		Model Name	Exploded diagram
		Drawing No.	BGP1505-02-17-BZ