



37	non-self-resetting thermal cut-out	KSD301-R/250V/16A	1
36	terminal	4 hole	2
35	relay	380-400V/25A	2
34	Heating element	230V 5000W	6
33	Re-set thermostat	KSD301/250V/16A	1
32	Adjustable thermostat	YT-WN16 250V/16A	1
31	Time delay thermostat	250V 10A K45	1
30	capacitance	CBB61/450V	1
29	Switch	250V 16A	1
28	Moter	400V	1
27	Fan	Ø350	1
26	Inner Casing	SECC	1
25	Outer casing	SPCC	1
24	Terminal support	SECC	1
23	Upper support of heating element	SECC	3
22	Under support of heating element	SECC	1
21	Inner casing holder	SECC	6
20	Cover of the grill	SPCC	1
19	Back cover of control box	SPCC	1
18	Front cover of control box	SPCC	1
17	Plug Panel	SPCC	1
16	Control panel	SPCC	1
15	Middle panel	SECC	1
14	Upper cover	SPCC	1
13	Components of the wind	SPCC	1
12	Back grill	SPCC	1
11	Front grill	SPCC	1
10	Right stand	SPCC	1
9	Left stand	SPCC	1
8	Metal handle	SPCC	1
7	Axis	SECC	1
6	Wheel	PP+PTR	2
5	Tube cap	PA	2
4	Fixed screws	M8*35mm	2
3	Sealing ring	PA	1
2	Industrial Plug	400V 63A	1
1	Knob	PA	2
Key No	Description	Material / Specifications	QTY

Project	BG-C30/3-19G(2022年状态)	Part No.			Parameter
Designer		Standard	Units	m m	
Check		Approval	Scale		
Ningbo Baogong Electrical Appliance Co.,Ltd.			Model Name	Exploded diagram	
			Drawing No.	BG-C30/3-19G-BZ	